

2500 Specifications

Motor

800 Newtons

R.P.M.: 1,625

Thermal Protection: Automatic

Lubrication: Permanent

Drive Mechanism

Drive Means: Full Reinforced Drive Belt

Reduction Means: Gear 16:1

Door Linkage: Adjustable Door Arm

Logic Type

Solid-State Micro-Controller with Built-in Surge Suppressor

Dimensions

Installed Length: 120 1/2"

Maximum Door Opening: 7'6"

Travel Rate: Approximately 7"/Second

Headroom Clearance Required: 2"

*Up to 10' with optional 8' or 10' rails

Shipping Weight

Head: 28 lbs.

Rail: 17 lbs.

Adjustments

Force: Independent External Up and Down

Limit: Internal/External

Electrical

Voltage: 120 VAC, 60 Hz

Wattage: 540

Current Rating: 4.5

U.L. Listings: Yes

Length of Line Cord: 6 Foot (3-prong)

Security+™ Radio Controls

Coding System: Smart Receiver Code Button and Indicator Light

Operating Range: 150 ft. Approximately

Operating Temperature: -40°F to 150°F

Battery (Remote Control): 3-Volt Lithium Battery

Frequency: 390 MHz

973W Designer Burlled Walnut 3-Button Remote

Security+™ Anti-Burglary Coding

Lighting System

Number of Bulbs: 2

Maximum Wattage: 100

Length of Light Delay: Adjustable

Type of Light Delay: Solid-State

Convenience/Safety

The Protector System®

Emergency/Quick Release

Automatic Trolley Reconnect

Ventilation/Pet Opening

Down Safety Reverse

Up Safety Stop

Door Open/Beam Broken/Lights On

Program Remote from Multi-Function Control Panel

PosiLock™

Open/Close/Stop Door from 973W Designer Burled Walnut 3-Button Remote

Materials

Chassis: Steel

Rail: Solid-Steel T

Trolley: Steel

Cartons

Number of Cartons: 2

Carton 1 Dimensions: 20" x 12" x 10"

Carton 1 Contents:

Multi-Function Control Panel

973W Designer Burled Walnut 3-Button Remote, Garage Door Opener

Head, The Protector System®

Carton 2 Dimensions: 10'4" x 5" x 5"

Carton 2 Contents: Assembled Solid-Steel T-Rail

*****WARNING:** Garage doors and openers can be dangerous if not properly installed, tested and operated. Children should be supervised by an adult whenever in or around the garage area.

Lifetime Motor and Belt Warranty. 5 years on all other parts. For more information, refer to owner's manual. LiftMaster Garage Door Openers meet all current state and federal regulations and UL safety regulations as of date of manufacture.